

EUROLINE safes

mark II



New DESIGN, same proven Quality

A unique low profile front face and a more shallow body offers more interior space conventional designs without compromising security.

-3 sizes to choose from

Body and Door

The body and door are constructed with Megasafe's high-security complex composite matrix material forming a barrier able to resist attacks by various mechanical and electro-mechanical tools available today.

-Body barrier thickness: 2" (50mm)

-Door barrier thickness: 1.57" (40mm)

Features:

Manganese anti-drill hard steel plates protect the locks and vital areas

A smooth operating gear driven mechanism extends chrome plated bolts 1.2" 30mm into individual bolt chambers.

An adjustable shelf standard on all 3 models allow vertical adjustment by every 2" (50mm)

Hinges are manufactured of a solid steel block and allow opening the door to 180°

2 holes for anchoring on bottom of the safe for securely bolting down the safe to the floor

Lock options:

The euroline safes are fitted with 2 independent high-security locks: a user friendly electronic lock and a double bitted mechanical key lock together they offer a superior level of security

Electronic lock features:

1 Manager Code

1 User Code

Time Delay function up to 99min can be optionally set which enable a delayed opening of the safe lock and door if needed

Wrong try penalty delay resists possible code guessing

Fire Resistant

the safes composite construction offers limited fire protection of 1 hr



REAL SECURITY BUILT TO A HIGHER STANDARD

High-Security Residential /Small Business Safe



mark II

*the perfect Security Solution for your home or business
.....with style*



size 40

size 65

size 75

Locking options:



Digital Combination Lock



7 lever Kaba-Mauer Key Lock

Dimensions & Weights:

| MODEL | INSIDE DIMENSIONS | | | OUTSIDE DIMENSIONS | | | APPROX. WEIGHT |
|---------------------------|-------------------|------------------|------------------|--------------------|------------------|------------------|---------------------|
| | H | W | D* | H | W | D* | |
| MK 1216 Size 40 | 12.0" (300mm) | 16.0" (400mm) | 11.0" (280mm) | 16.0" (400mm) | 19.7" (500mm) | 17.0" (440mm) | 297 lbs (135 kg) |
| MK 2116 Size 65 | 21.0" (550mm) | 16.0" (400mm) | 11.0" (280mm) | 25.6" (650mm) | 19.7" (500mm) | 17.0" (440mm) | 420 lbs (190 kg) |
| MK 2620 Size 75 | 25.6" (650mm) | 19.7" (500mm) | 13.4" (340mm) | 29.5" (750mm) | 23.6" (600mm) | 19.7" (500mm) | 564 lbs (256 kg) |

*Add 2" (50mm) to outside depth for handle and locks



9V Battery Drawer is located conveniently in the inner side of the safe's door. The lock notifies you when the battery is weak with 6 continuous beeps just after entering your code. As a safety, the lock can always be alternatively powered up from the front face of the lock so you never have to worry of being locked out do to a low battery.

Authorized Dealer:

In effort to continuously innovate and develop high-security products, the manufacturer reserves the right to incorporate any improvements and alter any specifications without prior notice.